

# FILTLAB



## EXTRUDE ALUMINIUM FRAME

- Standard synthetic pre-filter come with rod retainer
- Customize size is possible
- Low Initial Pressure Lost
- Easy to install and long service life
- Reusable Frame
- No Glue / Adhesive

## SPECIFICATION

Nominal Size W x H x D (in)	Actual Size W x H x D (mm)	Average Arrestance Efficiency (%)	Filter Class EN779	Rated Air Flow (CMH)	Initial Pressure Drop (Pa)
24 x 24 x 1	592 x 592 x 22	80	G2	3400	22
24 x 24 x 2	592 x 592 x 47				
24 x 24 x 4	592 x 592 x 96				
24 x 24 x 1	592 x 592 x 22	90	G3		29
24 x 24 x 2	592 x 592 x 47				
24 x 24 x 4	592 x 592 x 96				
24 x 24 x 1	592 x 592 x 22	93	G4		41
24 x 24 x 2	592 x 592 x 47				
24 x 24 x 4	592 x 592 x 96				

## Operating Condition

Temperature	80°C
Humidity Limit	100%RH

## Material

Frame	Aluminum Extrusion
Filter Media	Synthetic Fiber
Support Grid	Galvanized Steel Rod
Washable	Yes